



OVERRUN BRAKE



SIMPLE CONTROL



HAULBACKLINE (optional)



EASY ACCESSIBLE



CLEAN ANCHORING





The **K 300-H** is a yarder for uphill logging with an optional haulbackline drum (K303H). Also for downhill logging and for flat terrain. It assures easy handling, reliable and rugged design, as well as very short set up and dismantling times.

SPECIFICATIONS

LINE CAPACITY		STANDARD	ALTERNATIVE	LINE PULL	
Skyline		1650' Ø 9/16" · 500 m Ø 14 mm swaged	1320' Ø 5/8" · 420 m Ø 15 mm swaged	Skyline	4.48 t · 44 kN
Mainline		2260' Ø 5/16" · 550 m Ø 8 mm swaged	1480' Ø 3/8" · 450 m Ø 9,5 mm swaged	Mainline	1.83 t · 18 kN
Haulbackline		2900' Ø 3/8" · 970 m Ø 9 mm	2050' Ø 7/16" · 800 m Ø 10 mm	Haulbackline	1.83 t · 18 kN
Guyline		3x100' Ø 5/8" / 2x30' 3x30 m Ø 16 mm / 2x10 m extensions	4x100' Ø 5/8" / 2x30' 4x30 m Ø 16 mm / 2x10 m extensions		

LINE SPEED

Without payload	user defined by brake
With payload	up to 1115 ft/min · 340 m/min

POWER STATION

- Deutz 4-cylinder diesel engine with 101 HP (75 kW)
- Emission class EU-STAGE II
- Continuous hydrostatic transmission for all winches
- Hydraulically operated single disk dry clutches on the skyline / mainline drum and oil motor on the haulbackline drum

TOWER

Standard	24' · 7.2 m
Tower extension	28' · 8.4 m
Operating range	on the left side of the yarder

FEATURES

- Dead man's circuit
- Compact and reliable
- Lightweight and compact trailer unit
- Often proven because of the robust and simple design
- Overrun brake
- Foldable tower 1.2 m (optional)
- Available as a uphill- and downhill yarder (optional)

CARRIAGE

	SKA 1	SKA 1-Z	USKA 1,5
	Ø 1/2"-1" · Ø 12-24 mm	Ø 1/2"-1" · Ø 12-24 mm	Ø 9/16"-1" · Ø 14-24 mm
	Ø 5/16"-7/16" · Ø 8-11 mm	Ø 5/16"-7/16" · Ø 8-11 mm	Ø 3/8"-7/16" · Ø 9-11 mm
	approx. 350 lbs · 160 kg	approx. 420 lbs · 190 kg	approx. 760 lbs · 345 kg
	approx. 1.5 t	approx. 1.5 t	approx. 1.5 t

